

TechKut FT703G Chlorinated Machining and Grinding Oil

DESCRIPTION:

Key Features:

TechKut FT703G is a chlorinated straight oil formulated for the machining and grinding of ferrous metals. Engineered with a synergistic extreme pressure (EP) additive package, it delivers superior performance over conventional cutting oils—ensuring exceptional surface finishes and extended tool life.

TYPICAL PROPERTIES (NOT SPECIFICATIONS):

Appearance	Clear Amber Oil
Density	0.8960@60°F
Viscosity (cSt at 40°C)	21 cSt
Copper Corrosion	4C

FEATURES / BENEFITS:

- Synergistic EP package for high demand lubrication requirements

MIX / APPLICATION & USE:

Use neat

TechKut FT703G Chlorinated Machining and Grinding Oil

HEALTH & SAFETY:

TechKut FT703G is available at our Brighton, Michigan facility in 55-gallon drums, 330 gallon totes and 5 gallon pails.

Storage And Handling: See Safety Data Sheet Before Use. Use at room temperature. Store at temperatures between 45°- 90°F. Do not expose to extreme high temperature due to container rupture. Do not pressurize drum or reuse empty container. Follow all safety regulations on label.

Non-Warranty: While the information and recommendations sent forth herein are believed to be accurate as of the date thereof, Fortech Products, Inc. makes no warranty with respect thereto and disclaims all liability for reliance therein.

Last Updated: 1/20/2025