


TechLube FT 413VL Vanishing Oil

DESCRIPTION:

TechLube FT 413VL Vanishing Oil is a solvent-based lubricant with an additional lubricant additive that imparts a thin, imperceptible film of lubricant that facilitates a clean die release on both thin sheet and roll stock. The product may be applied by brush, roller, spray, dip tank, slush or flow coat and generally dries in one to four hours depending on film thickness.

This post is also available in: 

TYPICAL PROPERTIES (NOT SPECIFICATIONS):

Appearance	Clear Liquid
Specific Gravity @ 60oF, ASTM D-1298	0.76
Pounds Per. Gallon, ASTM D-1298	6.5 @ 60°F
Flash Point, ASTM D-93	>130°F

FEATURES / BENEFITS:

- Non-Staining
- Easily Applied
- Easily Removed
- Additional Lubrication

MIX / APPLICATION & USE:

TechLube FT 413VL Vanishing Oil

HEALTH & SAFETY:

TechLube FT 413VL Vanishing Oil is available at our Brighton, Michigan facility in 55-gallon drums, 330 gallon totes and 5 gallon pails.

Storage And Handling: See Safety Data Sheet Before Use. Use at room temperature. Store at temperatures between 45°- 90°F. Do not expose to extreme high temperature due to container rupture. Do not pressurize drum or reuse empty container. Follow all safety regulations on label.

Non-Warranty: While the information and recommendations sent forth herein are believed to be accurate as of the date thereof, Fortech Products, Inc. makes no warranty with respect thereto and disclaims all liability for reliance therein.

Last Updated: 7/5/2022